

Thermal and Acoustic Wall

Description

ecoinsulation® Thermal and Acoustic Wall insulation with DriTherm® technology is made using a silicone treatment that is added to the glasswool during manufacture to upgrade the moisture resistance of the insulation, and provide guaranteed water resistance for 50 years.

ecoinsulation® Thermal and Acoustic Wall insulation is made using:

- Up to 80% recycled glass
- ECOSE® Technology - binder with no added formaldehyde
- TwinTech® - dual forming technique for a smooth finish on both sides.



Product Range

Product code	R-Value (m ² K/W)	Lambda (W/mK)	Density (kg/m ³)	Thickness (mm)	Width (mm)	Length (mm)	Area per pack (m ²)	Pieces per pack	Pack weight (kg)
707862	2.2	0.043	10.8	90	430	1160	14.5	29	14.1
683713	2.2	0.043	10.8	90	580	1160	19.5	29	19.0
683693	2.3	0.039	12.4	90	600	1160	17.4	25	19.5
683707	2.4	0.038	14.6	90	570	1160	13.2	20	17.4
SoundShield									
707756	2.6	0.036	20.1	90	430	1160	7.5	15	13.5
707749	2.6	0.036	20.1	90	580	1160	9.4	14	17.0
683696	2.6	0.035	20.1	90	600	1160	9.7	14	17.6
707751	2.8	0.033	30.7	90	430	1160	5.0	10	12.2
707771	2.8	0.033	30.7	90	580	1160	6.7	10	16.5
140mm High Performance									
683708	3.2	0.044	9.4	140	580	1160	14.8	22	19.5
683709	3.6	0.039	13.4	140	570	1160	9.9	15	18.6
707768	4.1	0.035	22.6	140	580	1160	6.1	9	19.2

All dimensions are nominal.

Technical Data

Water Vapour Absorption

- Less than 5% by weight.

Corrosion Resistance

- No greater than sterile cotton.

Microbial Growth

- Does not support microbial growth.

Fire Hazard Properties (AS/NZS 1530.3)

- Ignitability: 0, Spread of flame: 0.

Heat Evolved: 0, Smoke Developed: 0-1.

Combustibility (AS 1530.1)

- Non-combustible.

Performance

Thermal

AS/NZS 4859.1 (2018).

Thermal and Acoustic Wall

Specification Compliance

AS/NZS 4859.1 (2018) Materials used in the Thermal Insulation of Buildings and comply with the New Zealand Building Code requirements: B2 – Durability, E3 – External Moisture, F2 – Hazardous Building Materials, and H1 – Energy Efficiency.

ecoinsulation® Thermal and Acoustic Wall range is an acceptable solution in terms of the New Zealand Building Code. This product is designed for use in timber and metal frame applications in new and existing domestic and commercial buildings.

Bio-solubility

The formulation used for **ecoinsulation**® glasswool has been independently assessed to meet the requirements of the stringent Note Q standard (and is therefore consistent with the highest Australian and New Zealand industry standards), and also assessed by Knauf Insulation against the criteria of the Australian Safety and Compensation Council ASCC Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008 3rd Edition]. As a result of this assessment, **ecoinsulation**® glasswool is not classified as hazardous according to the NOHSC criteria.

Environmental

ecoinsulation® glasswool represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

Features and Benefits

Proven Performance

- Preferred by professional installers concerned with quality, appearance and productivity.
- Excellent acoustical properties reduce sound transmission in the home when properly installed in walls, ceiling and floor systems.

Durability

- **ecoinsulation**® glasswool insulation is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.
- DriTherm® technology - silicone treated for increased durability.

Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials that feel good, cut easily and can be installed fast.
- Low dust for easier handling and increased productivity.

Convenient Packaging, Easier Handling

- **ecoinsulation**® glasswool is packaged in a strong, white poly bag that offers excellent protection from abuse, dust and moisture.
- **ecoinsulation**® glasswool packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

Superior Service and Support

- We are focused on providing first class customer service, producing high quality products and 'in full on time' deliveries.
- We are committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.

ecoinsulation
energy and installation



Eco Insulation Energy
and Installation Limited
PO Box 217063, Botany Junction,
Auckland, 2164



www.ecoinsulation.co.nz



products@ecoinsulation.co.nz



0800 400 326